

TECHNICAL SPECIFICATION

MODEL	PCMK 3 HE (ANSI)
Model No. (SKU)	PCMK3HE803
DIMENSIONS	
Layout	87Key ANSI
Length	355mm (13.9in)
Width	127mm (5in)
Height	37mm (1.45in)
Weight	963g (± 1g) / 33.9oz
SWITCH	
Type	Linear
Initial Force	30±7gf
Total travel	4.1±0.2mm
Initial Magnetic Flux	75±15Gs
Bottom-out Magnetic Flux	700±80Gs
Lifespan	150 million keystrokes
PACKAGE CONTENTS	
Keyboard x 1	
ID Tag x 1	
USB-C Cable x 1	
Switch + Keycap puller x 1	
Extra Switches x 3	
Hard Dust Cover x 1	
Keyboard Pouch x 1	
CERTIFICATION	CE FC R-R-APx-PCMK3HE801



TECHNICAL
80% ANSI Keyboard(87 KEY)
Hall Effect Magnetic switch
True 8K Polling Rate
Ultra Fast 35K Scan Rate
6-Layer PCB
9-Multi MCU System
RT Resolution 0.01mm
Latency 0.1ms
Rapid Trigger
Web based Software 'Bibimbap'
RGB lighting effects
Triple absorption structure
Adjustable Actuation 0.1mm-4mm
Support for 3 Profiles
Aluminum Alloy Plate and Transparent body
PBT Double-shot keycaps
REQUIREMENT
USB 2.0 port or higher
Windows 7 or higher
Mac OS x 10.10 or later